



# 成形機仕様一覧

(2010年4月現在)



機番	型締力	スクリュウ径	射出体積	型締ST	最小型厚	最大型開き	タイプ-間隔	ダイプレート	エジェクタST
	ton	mm	cm <sup>3</sup> /shot	mm	mm	mm	mm	mm	mm
A1	40	26	49	300	200	500	280X280	420X420	60
A2	60	32	90	430	170	600	315X315	468X468	70
A3	80	36	148	350	*1 160	*1 685	375X375	535X535	75
A4	80	40	182	350	*1 160	*1 685	375X375	535X535	75
A5	120	45	254	400	*1 170	*1 700	410X410	600X600	85
A6	120	36	148	520	180	700	410X410	600X600	85
A7	161	45	254	470	*1 200	*1 880	460X460	685X685	100
A8	80	40	182	350	*1 160	*1 685	375X375	535X535	75
A9	120	40	201	400	*1 170	*1 700	410X410	600X600	85
A10	140	50	353	600	250	850	480x480	700x700	90
A11	161	50	353	470	*1 200	*1 880	460X460	685X685	100
A12	179	45	286	700	250	950	530x530	770x770	110
B1	180	50	353	530	*1 220	*1 950	530X530	770X770	110
B2	179	50	353	700	250	950	530x530	770x770	110
B3	260	63	701	820	280	1100	615x615	905x905	130
B4	180	50	353	530	*1 220	*1 950	530X530	770X770	110
B5	250	64	514	575	*1 265	*1 985	570X470(V)	825X725(V)	129
B6	161	50	353	470	*1 200	*1 880	460X460	685X685	100
B7	161	50	353	470	*1 200	*1 880	460X460	685X685	100
B8	260	56	554	820	280	1100	615x615	905x905	130
B9	360	71	1109	960	300	1260	710X710	1030X1030	150
C1	212	56	505	550	*1 265	*1 1050	570X570	825X825	120
C2	260	63	701	600	*1 265	*1 1150	615X615	905X905	130
C3	456	90	2004	1025	375	1400	820x820	1190x1190	160
		80	1583						
D1	30	26	49	200	200	400			50
D2	60	32	90	220	200	420	Φ830*	560X350	50

D1,D2は縦型ロータリ成形機

